



SD500-ARM

Addressable Relay Module


The SD500-ARM is an addressable device that adds two Form C contacts to the Farenhyt addressable system. The contacts are rated at 2.0 amps @ 30 VDC or .6 amp @ 120 VAC.

The SD500-ARM allows you to control a wide variety of normally open and normally closed applications, including elevator recall, door closing, fan operation, and auxiliary notification. And, because the relay module is addressable, these applications can be located at any point in the signaling line circuit.

COMPATIBILITY

The SD500-ARM is compatible with the following Honeywell Silent Knight FACPs:

- 6820:** Addressable fire alarm control panel with up to 1,110 addressable points
- 6820EVS:** Addressable fire alarm control panel with an emergency mass notification system, up to 1,110 addressable points
- 6808:** Addressable fire alarm control panel with up to 198 addressable points
- 6700:** Addressable fire alarm control panel with up to 100 addressable points
- 5820XL:** Addressable fire alarm control panel
- 5820XL-EVS:** Addressable fire alarm control panel with an emergency communication systems
- 5808:** Addressable fire alarm control panel
- 5700:** Addressable fire alarm control panel




SD500-ARM

FEATURES & BENEFITS

- Two sets of Form C contacts. (Double pull/Double Throw relays)
- Contacts are rated at 2A @ 30 VDC or .6A @ 120 VAC.
- Up to 127 relays can be used on each SLC loop.
- Relay programming is completely flexible—can be mapped to zone conditions.
- Polling LED visible through cover plate.
- UL listed, complies with NFPA 72.

SD500-ARM Technical Specifications



TYPICAL MOUNTING FOR SD500-ARM

SPECIFICATIONS

PHYSICAL:

Mounting: 4" square

ENVIRONMENTAL

Operating Temperature: 32°F to 120°F (0°C to 49°C)

Humidity: 0 to 93% relative humidity (non condensing)

ELECTRICAL:

Standby Current: .55 mA

Alarm Current: .55 mA

Contact Rating: Form C
2A @ 30VDC or .6A @ 120VAC

ORDERING INFORMATION

SD500-ARM: Addressable relay module

AGENCY LISTINGS AND APPROVALS

UL Listed

CSFM

MEA 429-92-E, Vol 9

FM approved

For a complete listing of all compliance approvals and certifications, please visit www.silentknight.com.

Microsoft, Windows, and the Windows Logo are registered trademarks or trademarks of Microsoft Corporation.

Silent Knight® and Honeywell® are registered trademarks of Honeywell International, Inc.

This document is not intended to be used for installation purposes. We try to keep our product information up-to date and accurate. We cannot cover all specific applications or anticipate all requirements. All specifications are subject to change without notice.

For Technical Support, call 800-446-6444.

For more information

Learn more about Honeywell Silent Knight and other products by visiting www.silentknight.com

Honeywell Silent Knight

12 Clintonville Road
Northford, CT 06472
800-328-0103

350218 | G | 11/17
© 2017 Honeywell International Inc.

